

CADREX EV 1400

Vanishing Neat Oil

DESCRIPTION

CADREX EV 1400 is a chlorine and Sulphur free vanishing fluid, specifically designed for the forming and cutting of steel, stainless steel, aluminium and copper alloys.

CADREX EV 1400 complies with US FDA status and meets the requirements of the food industry.

APPLICATIONS

CADREX EV 1400 is a vanishing lubricant that is mainly used for the forming and cutting of steel, aluminum and copper alloys.

CADREX EV 1400 is best suited for non-severe operations on sheets with a thickness up to 2mm.

CADREX EV 1400 can be used by low pressure spraying, roller, impregnation or by dipping.

ADVANTAGES

- Low smell.
- Good wettability.
- Fast evaporation.
- Leaves no residues and thermodegradable.
- Application : low pressure spraying, roller, impregnation by dipping.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	CADREX EV 1400
Color	-	Visual	Colorless
Aspect	-		Liquid
Density at 20°C (68°F)	-	ISO 12.185	0.785
Viscosity at 40°C (104°F)	mm ² /s	ISO 3104	1.4
Flash point	°C	ASTM D32	62.0
Copper Strip Corrosion	-	NTF M 07105	1a
Vapour Pressure	kPa		0.01 at 20°C / 0.03 at 37.8°C

These characteristics are given only for information and can be updated over time.



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.